

## Canopy Kits

**198-00-0044: 5" Feed Canopy w/ Cable**

**198-00-0041: 5" Canopy w/ Cable**

**198-00-0042: 2" Canopy w/ Cable**

### 1~ & 2~ track canopy kits

**Canopy:** Steel powder coated 5" & 2" OD canopy x .20" H x .030 thick material. Canopy is equipped with 25/64" OD mounting center hole. Feed canopy (198-00-0044) power out hole has a diameter of 7/8" (22mm) that accepts strain relief bushing. (Supplied by others)

**Colors:** -01: White, -02: Black

**Cable:** Cable has a diameter of 1/16" and a length of 48". One end of cable is clear of any burrs to allow threading through grippers. The opposite end has a die-cast stop end to prevent cable from pulling through grippers. **When field cutting cable, the end without cable stop is the only end to be cut in the field to desired length.**

**Gem Bar:** Equipped with a 1/4"-20" countersunk hole that secures to "J" Box (supplied by others) **Gem box not available on 2" canopy covers.**

**198-00-0004-01** (T-Bar clip) recommended to secure 2" canopy . **(Order separate)**


**Coupler:** Two piece cable coupler secures to counter sunk screw in Gem Bar after cable with stop has been threaded through.

**Gripper:** 2 piece gripper accepts cable and locks in place. Any access cable would be cut from this end. Lock nut secures threaded part of gripper to clip or coupler. **(198-00-0001 or 198-00-0002)**


This information is subject to change without notice.



**198-00-0004-01 (T-Bar clip) recommended to secure 2" canopy . Order separate.**



**198-00-0044- 198-00-0041- 198-00-0042-**



**Suspended Cable Support secured to Pendant Clip and Track.** Clips and Mechanical couplers are ordered separate.

**198-00-0001:** Pendant Clip (2")

**198-00-0002:** Mechanical Coupler (4")

(Colors: -01: White , -02: Black

**NOTE: "J" Box, drop ceiling T bar and strain releif bushing supplied by others.**

